

System.TimeSpan Structure

```
[ILAsm]
.class public sequential sealed serializable TimeSpan extends
System.ValueType implements System.IComparable,
System.IComparable`1<valuetype System.TimeSpan>,
System.IEquatable`1<valuetype System.TimeSpan>

[C#]
public struct TimeSpan: IComparable, IComparable<TimeSpan>,
IEquatable<TimeSpan>
```

Assembly Info:

- *Name:* mscorlib
- *Public Key:* [00 00 00 00 00 00 00 00 04 00 00 00 00 00 00 00]
- *Version:* 2.0.x.x
- *Attributes:*
 - CLSCompliantAttribute(true)

Implements:

- **System.IComparable**
- **System.IComparable<System.TimeSpan>**
- **System.IEquatable<System.TimeSpan>**

Summary

Represents an interval of time.

Inherits From: System.ValueType

Library: BCL

Thread Safety: All public static members of this type are safe for multithreaded operations. No instance members are guaranteed to be thread safe.

Description

The System.TimeSpan structure represents an interval of time with values ranging from System.Int64.MinValue to System.Int64.MaxValue 100-nanosecond *ticks*.

[*Note:* The value of a System.TimeSpan is represented internally as a number of 100-nanosecond ticks. Both the specification of a number of ticks and the value of a System.TimeSpan can be positive or negative.

A System.TimeSpan can be represented as a string in the format "[...]d.hh:mm:ss.ff"

1 where "-" is an optional sign for negative `System.TimeSpan` values, the "d" component is
2 days, "hh" is hours, "mm" is minutes, "ss" is seconds, and "ff" is fractions of a second.
3 For example, a `System.TimeSpan` initialized with 10^{13} ticks would be represented as
4 "11.13:46:40", which is 11 days, 13 hours, 46 minutes, and 40 seconds.

5
6 Due to a varying number of days in months and years, the longest unit of time that is
7 used by this structure is the day.

8
9]

10

1 TimeSpan(System.Int64) Constructor

```
2 [ILAsm]  
3 public rtspecialname specialname instance void .ctor(int64 ticks)  
4 [C#]  
5 public TimeSpan(long ticks)
```

6 Summary

7 Constructs and initializes a new `System.TimeSpan` with the specified number of ticks.

8 Parameters

| Parameter | Description |
|--------------|--|
| <i>ticks</i> | A <code>System.Int64</code> that specifies the number of ticks with which to initialize the new <code>System.TimeSpan</code> . |

1 TimeSpan(System.Int32, System.Int32, 2 System.Int32) Constructor

```
3 [ILAsm]  
4 public rtspecialname specialname instance void .ctor(int32 hours, int32  
5 minutes, int32 seconds)  
  
6 [C#]  
7 public TimeSpan(int hours, int minutes, int seconds)
```

8 Summary

9 Constructs and initializes a new `System.TimeSpan` with the specified numbers of hours,
10 minutes, and seconds.

11 Parameters

| Parameter | Description |
|----------------|--|
| <i>hours</i> | A <code>System.Int32</code> that specifies the number of hours with which to initialize the new <code>System.TimeSpan</code> . |
| <i>minutes</i> | A <code>System.Int32</code> that specifies the number of minutes with which to initialize the new <code>System.TimeSpan</code> . |
| <i>seconds</i> | A <code>System.Int32</code> that specifies the number of seconds with which to initialize the new <code>System.TimeSpan</code> . |

15 Description

16 The specified *hours*, *minutes*, and *seconds* are converted to ticks, and that value is used
17 to initialize the new `System.TimeSpan`.

18 Exceptions

| Exception | Condition |
|---|--|
| System.ArgumentOutOfRangeException | The parameters specify a <code>System.TimeSpan</code> value less than <code>System.TimeSpan.MinValue</code> or |

| | |
|--|--|
| | greater than <code>System.TimeSpan.MaxValue</code> . |
|--|--|

1

2

3

1 TimeSpan(System.Int32, System.Int32, 2 System.Int32, System.Int32, System.Int32) 3 Constructor

```
4 [ILAsm]  
5 public rtspecialname specialname instance void .ctor(int32 days, int32  
6 hours, int32 minutes, int32 seconds, int32 milliseconds)  
  
7 [C#]  
8 public TimeSpan(int days, int hours, int minutes, int seconds, int  
9 milliseconds)
```

10 Summary

11 Constructs and initializes a new `System.TimeSpan` with the specified numbers of days,
12 hours, minutes, seconds, and milliseconds.

13 Parameters

| Parameter | Description |
|---------------------|---|
| <i>days</i> | A <code>System.Int32</code> that specifies the number of days with which to initialize the new <code>System.TimeSpan</code> . |
| <i>hours</i> | A <code>System.Int32</code> that specifies the number of hours with which to initialize the new <code>System.TimeSpan</code> . |
| <i>minutes</i> | A <code>System.Int32</code> that specifies the number of minutes with which to initialize the new <code>System.TimeSpan</code> . |
| <i>seconds</i> | A <code>System.Int32</code> that specifies the number of seconds with which to initialize the new <code>System.TimeSpan</code> . |
| <i>milliseconds</i> | A <code>System.Int32</code> that specifies the number of milliseconds with which to initialize the new <code>System.TimeSpan</code> . |

17 Description

18 The specified *days*, *hours*, *minutes*, *seconds*, and *milliseconds* are converted to ticks,
19 and that value is used to initialize the new `System.TimeSpan`.

1 **Exceptions**

2

3

| Exception | Condition |
|---|---|
| System.ArgumentOutOfRangeException | The parameters specify a <code>System.TimeSpan</code> value less than <code>System.TimeSpan.MinValue</code> or greater than <code>System.TimeSpan.MaxValue</code> . |

4

5

6

1 TimeSpan(System.Int32, System.Int32, 2 System.Int32, System.Int32) Constructor

```
3 [ILAsm]  
4 public rtspecialname specialname instance void .ctor(int32 days, int32  
5 hours, int32 minutes, int32 seconds)  
  
6 [C#]  
7 public TimeSpan(int days, int hours, int minutes, int seconds)
```

8 Summary

9 Constructs and initializes a new `System.TimeSpan` with the specified numbers of days,
10 hours, minutes, and seconds.

11 Parameters

| Parameter | Description |
|----------------|--|
| <i>days</i> | A <code>System.Int32</code> that specifies the number of days with which to initialize the new <code>System.TimeSpan</code> . |
| <i>hours</i> | A <code>System.Int32</code> that specifies the number of hours with which to initialize the new <code>System.TimeSpan</code> . |
| <i>minutes</i> | A <code>System.Int32</code> that specifies the number of minutes with which to initialize the new <code>System.TimeSpan</code> . |
| <i>seconds</i> | A <code>System.Int32</code> that specifies the number of seconds with which to initialize the new <code>System.TimeSpan</code> . |

14 Description

16 The specified *days*, *hours*, *minutes*, and *seconds* are converted to ticks, and that value
17 is used to initialize the new `System.TimeSpan`.

18 Exceptions

| Exception | Condition |
|-----------|-----------|
|-----------|-----------|

System.ArgumentOutOfRangeException

The parameters specify a `System.TimeSpan` value less than `System.TimeSpan.MinValue` or greater than `System.TimeSpan.MaxValue`.

1
2
3

1 TimeSpan.MaxValue Field

```
2 [ILAsm]  
3 .field public static initOnly valuetype System.TimeSpan MaxValue  
  
4 [C#]  
5 public static readonly TimeSpan MaxValue
```

6 Summary

7 Returns a System.TimeSpan whose value is the maximum value for the
8 System.TimeSpan type.

9 Description

10 This field is read-only.

11
12 This field is a System.TimeSpan containing System.Int64.MaxValue ticks, the maximum
13 System.TimeSpan value. The string representation of this value is positive
14 10675199.02:48:05.4775807.

1 TimeSpan.MinValue Field

```
2 [ILAsm]  
3 .field public static initOnly valuetype System.TimeSpan MinValue  
4 [C#]  
5 public static readonly TimeSpan MinValue
```

6 Summary

7 Returns a `System.TimeSpan` whose value is the minimum value for the
8 `System.TimeSpan` type.

9 Description

10 This field is read-only.

11
12 This field is a `System.TimeSpan` containing `System.Int64.MinValue` ticks, the minimum
13 `System.TimeSpan` value. The string representation of this value is negative
14 10675199.02:48:05.4775808.

1 TimeSpan.TicksPerDay Field

```
2 [ILAsm]  
3 .field public static literal int64 TicksPerDay = 864000000000  
4 [C#]  
5 public const long TicksPerDay = 864000000000
```

6 Summary

7 Represents the number of ticks in 1 day.

8 Description

9 The value of this constant is 864 billion (8.64×10^{11}).

1 TimeSpan.TicksPerHour Field

```
2 [ILAsm]  
3 .field public static literal int64 TicksPerHour = 36000000000  
4 [C#]  
5 public const long TicksPerHour = 36000000000
```

6 Summary

7 Represents the number of ticks in 1 hour.

8 Description

9 The value of this constant is 36 billion (3.6×10^{10}).

1 TimeSpan.TicksPerMillisecond Field

```
2 [ILAsm]  
3 .field public static literal int64 TicksPerMillisecond = 10000  
4 [C#]  
5 public const long TicksPerMillisecond = 10000
```

6 Summary

7 Represents the number of ticks in 1 millisecond.

8 Description

9 The value of this constant is 10 thousand (10^4).

1 TimeSpan.TicksPerMinute Field

```
2 [ILAsm]  
3 .field public static literal int64 TicksPerMinute = 600000000  
4 [C#]  
5 public const long TicksPerMinute = 600000000
```

6 Summary

7 Represents the number of ticks in 1 minute.

8 Description

9 The value of this constant is 600 million (6×10^8).

1 TimeSpan.TicksPerSecond Field

```
2 [ILAsm]  
3 .field public static literal int64 TicksPerSecond = 10000000  
4 [C#]  
5 public const long TicksPerSecond = 10000000
```

6 Summary

7 Represents the number of ticks in 1 second.

8 Description

9 The value of this constant is 10 million (10^7).

1

2

3

4

6

7

8

9

10

11

12

13

14

15

1 TimeSpan.Add(System.TimeSpan) Method

```
2 [ILAsm]  
3 .method public hidebysig instance valuetype System.TimeSpan Add(valuetype  
4 System.TimeSpan ts)  
  
5 [C#]  
6 public TimeSpan Add(TimeSpan ts)
```

7 Summary

8 Adds the specified `System.TimeSpan` to the current instance.

9 Parameters

| Parameter | Description |
|-----------|---|
| <i>ts</i> | A <code>System.TimeSpan</code> instance to add to the current instance. |

13 Return Value

15 A `System.TimeSpan` that represents the value of the current instance plus the value of
16 *ts*.

17 Exceptions

| Exception | Condition |
|---------------------------------|--|
| System.OverflowException | The sum of the value of the current instance and the value of <i>ts</i> is less than <code>System.TimeSpan.MinValue</code> or greater than <code>System.TimeSpan.MaxValue</code> . |

21 Example

23 This example demonstrates the `System.TimeSpan.Add` method.

24 [C#]
25

26 using System;

```
1 public class TimeSpanAddExample {
2     public static void Main() {
3         TimeSpan ts = new TimeSpan(Int32.MaxValue);
4         Console.WriteLine("The value of the timespan 'ts' is {0}", ts);
5         Console.WriteLine("ts.Add(ts) = {0}", ts.Add(ts));
6     }
7 }
```

8 The output is

9
10 The value of the timespan 'ts' is 00:03:34.7483647

11
12
13 ts.Add(ts) = 00:07:09.4967294

14

15

1 TimeSpan.Compare(System.TimeSpan, 2 System.TimeSpan) Method

```
3 [ILAsm]  
4 .method public hidebysig static int32 Compare(valuetype System.TimeSpan  
5 t1, valuetype System.TimeSpan t2)  
  
6 [C#]  
7 public static int Compare(TimeSpan t1, TimeSpan t2)
```

8 Summary

9 Returns the sort order of two System.TimeSpan structures.

10 Parameters

| Parameter | Description |
|-----------|--|
| <i>t1</i> | The first System.TimeSpan to compare. |
| <i>t2</i> | The second System.TimeSpan to compare. |

14 Return Value

16 The return value is a negative number, zero, or a positive number reflecting the sort
17 order of *t1* as compared to *t2*. For non-zero return values, the exact value returned by
18 this method is unspecified. The following table defines the return value:

| Value | Condition |
|---------------------|--------------|
| Any negative number | $t1 < t2$. |
| Zero | $t1 == t2$. |
| Any positive number | $t1 > t2$. |

1 TimeSpan.CompareTo(System.Object)

2 Method

```
3 [ILAsm]  
4 .method public final hidebysig virtual int32 CompareTo(object value)  
  
5 [C#]  
6 public int CompareTo(object value)
```

7 Summary

8 Returns the sort order of the current instance compared to the specified `System.Object`.

9 Parameters

| Parameter | Description |
|--------------|--|
| <i>value</i> | The <code>System.Object</code> to compare to the current instance. |

13 Return Value

15 The return value is a negative number, zero, or a positive number reflecting the sort
16 order of the current instance as compared to *value*. For non-zero return values, the
17 exact value returned by this method is unspecified. The following table defines the
18 return value:

| Value | Condition |
|---------------------|--|
| Any negative number | Current instance < <i>value</i> . |
| Zero | Current instance == <i>value</i> . |
| Any positive number | Current instance > <i>value</i> , or <i>value</i> is a null reference. |

20 Description

21 [Note: This method is implemented to support the `System.IComparable` interface.]
22
23

1 **Exceptions**

2

3

| Exception | Condition |
|---------------------------------|---|
| System.ArgumentException | <i>value</i> is not a <i>System.TimeSpan</i> and is not a null reference. |

4

5

6

1 TimeSpan.CompareTo(System.TimeSpan)

2 Method

```
3 [ILAsm]  
4 .method public final hidebysig virtual int32 CompareTo(valuetype  
5 System.TimeSpan value)  
  
6 [C#]  
7 public int CompareTo(TimeSpan value)
```

8 Summary

9 Returns the sort order of the current instance compared to the specified
10 System.TimeSpan.

11 Parameters

| Parameter | Description |
|--------------|---|
| <i>value</i> | The System.TimeSpan to compare to the current instance. |

15 Return Value

17 The return value is a negative number, zero, or a positive number reflecting the sort
18 order of the current instance as compared to *value*. For non-zero return values, the
19 exact value returned by this method is unspecified. The following table defines the
20 return value:

| Value | Condition |
|---------------------|------------------------------------|
| Any negative number | Current instance < <i>value</i> . |
| Zero | Current instance == <i>value</i> . |
| Any positive number | Current instance > <i>value</i> . |

22 Description

1 [Note: This method is implemented to support the
2 System.IComparable<System.TimeSpan> interface.]
3
4
5

1 TimeSpan.Duration() Method

```
2 [ILAsm]  
3 .method public hidebysig instance valuetype System.TimeSpan Duration()  
4 [C#]  
5 public TimeSpan Duration()
```

6 Summary

7 Returns a System.TimeSpan whose value is the absolute value of the current instance.

8 Return Value

9
10 A System.TimeSpan whose value is the absolute value of the current instance.

11 Exceptions

| Exception | Condition |
|--------------------------|--|
| System.OverflowException | The value of the current instance is System.TimeSpan.MinValue. |

15 Example

17 The following example demonstrates the System.TimeSpan.Duration method.

18 [C#]

```
20 using System;  
21 public class TimeSpanDurationExample {  
22     public static void Main() {  
23         TimeSpan ts = new TimeSpan(Int32.MinValue);  
24         Console.Write("The absolute value of TimeSpan {0} ", ts);  
25         Console.WriteLine("is {0}", ts.Duration());  
26     }  
27 }
```

28 The output is

29
30 The absolute value of TimeSpan -00:03:34.7483648 is 00:03:34.7483648

1 TimeSpan.Equals(System.TimeSpan, 2 System.TimeSpan) Method

```
3 [ILAsm]  
4 .method public hidebysig static bool Equals(valuetype System.TimeSpan t1,  
5 valuetype System.TimeSpan t2)  
  
6 [C#]  
7 public static bool Equals(TimeSpan t1, TimeSpan t2)
```

8 Summary

9 Determines whether two System.TimeSpan structures represent the same type and
10 value.

11 Parameters

| Parameter | Description |
|-----------|---|
| <i>t1</i> | The first instance of System.TimeSpan to compare for equality. |
| <i>t2</i> | The second instance of System.TimeSpan to compare for equality. |

14 Return Value

15 true if *t1* and *t2* represent the same value; otherwise, false.
16
17
18

1 TimeSpan.Equals(System.Object) Method

```
2 [ILAsm]  
3 .method public hidebysig virtual bool Equals(object value)  
4 [C#]  
5 public override bool Equals(object value)
```

6 Summary

7 Determines whether the current instance and the specified `System.Object` represent the
8 same type and value.

9 Parameters

| Parameter | Description |
|--------------|--|
| <i>value</i> | The <code>System.Object</code> to compare to the current instance. |

13 Return Value

15 `true` if *value* represents the same type and value as the current instance. If *value* is a
16 null reference or is not a `System.TimeSpan`, returns `false`.

17 Description

18 [Note: This method overrides `System.Object.Equals`.]
19
20
21

1 TimeSpan.Equals(System.TimeSpan) Method

```
2 [ILAsm]  
3 .method public hidebysig virtual bool Equals(valuetype System.TimeSpan  
4 obj)  
  
5 [C#]  
6 public override bool Equals(TimeSpan obj)
```

7 Summary

8 Determines whether the current instance and the specified `System.TimeSpan` represent
9 the same value.

10 Parameters

| Parameter | Description |
|--------------|--|
| <i>value</i> | The <code>System.TimeSpan</code> to compare to the current instance. |

14 Return Value

16 `true` if *value* represents the same value as the current instance; otherwise, `false`.

17 Description

18 [Note: This method is implemented to support the
19 `System.IEquatable<System.TimeSpan>` interface.]
20
21
22

The following member must be implemented if the ExtendedNumerics library is present in the implementation.

TimeSpan.FromDays(System.Double) Method

```
[ILAsm]  
.method public hidebysig static valuetype System.TimeSpan FromDays(float64  
value)  
  
[C#]  
public static TimeSpan FromDays(double value)
```

Summary

Returns a `System.TimeSpan` that represents the specified number of days where the specification is accurate to the nearest millisecond.

Parameters

| Parameter | Description |
|--------------|--|
| <i>value</i> | A <code>System.Double</code> that specifies the number of days with which the new <code>System.TimeSpan</code> is initialized. |

Return Value

A `System.TimeSpan` that represents *value*.

Description

value will only be considered accurate to the nearest millisecond.

If *value* is `System.Double.PositiveInfinity`, a `System.TimeSpan` with the value `System.TimeSpan.MaxValue` is returned. If *value* is `System.Double.NegativeInfinity`, a `System.TimeSpan` with the value `System.TimeSpan.MinValue` is returned.

Exceptions

| Exception | Condition |
|---------------------------------|--|
| System.OverflowException | The <code>System.TimeSpan</code> represented by <i>value</i> is greater than |

| | |
|---------------------------------|--|
| | System.TimeSpan.MaxValue or less than System.TimeSpan.MinValue. |
| System.ArgumentException | <i>value</i> is equal to System.Double.NaN. |

1
2
3

The following member must be implemented if the ExtendedNumerics library is present in the implementation.

TimeSpan.FromHours(System.Double) Method

```
[ILAsm]  
.method public hidebysig static valuetype System.TimeSpan  
FromHours(float64 value)  
  
[C#]  
public static TimeSpan FromHours(double value)
```

Summary

Returns a `System.TimeSpan` that represents the specified number of hours where the specification is accurate to the nearest millisecond.

Parameters

| Parameter | Description |
|--------------|---|
| <i>value</i> | A <code>System.Double</code> that specifies the number of hours with which the new <code>System.TimeSpan</code> is initialized. |

Return Value

A `System.TimeSpan` that represents *value*.

Description

value will only be considered accurate to the nearest millisecond.

If *value* is `System.Double.PositiveInfinity`, a `System.TimeSpan` with the value `System.TimeSpan.MaxValue` is returned. If *value* is `System.Double.NegativeInfinity`, a `System.TimeSpan` with the value `System.TimeSpan.MinValue` is returned.

Exceptions

| Exception | Condition |
|-----------|-----------|
|-----------|-----------|

| | |
|---------------------------------|---|
| System.OverflowException | The <code>System.TimeSpan</code> represented by <i>value</i> is greater than <code>System.TimeSpan.MaxValue</code> or less than <code>System.TimeSpan.MinValue</code> . |
| System.ArgumentException | <i>value</i> is equal to <code>System.Double.NaN</code> . |

1
2
3

The following member must be implemented if the ExtendedNumerics library is present in the implementation.

TimeSpan.FromMilliseconds(System.Double) Method

```
[ILAsm]  
.method public hidebysig static valuetype System.TimeSpan  
FromMilliseconds(float64 value)  
  
[C#]  
public static TimeSpan FromMilliseconds(double value)
```

Summary

Returns a `System.TimeSpan` that represents the specified number of milliseconds where the specification is accurate to the nearest millisecond.

Parameters

| Parameter | Description |
|--------------|--|
| <i>value</i> | A <code>System.Double</code> that specifies the number of milliseconds with which the new <code>System.TimeSpan</code> is initialized. |

Return Value

A `System.TimeSpan` that represents *value*.

Description

value will only be considered accurate to the nearest millisecond.

If *value* is `System.Double.PositiveInfinity`, a `System.TimeSpan` with the value `System.TimeSpan.MaxValue` is returned. If *value* is `System.Double.NegativeInfinity`, a `System.TimeSpan` with the value `System.TimeSpan.MinValue` is returned.

Exceptions

| Exception | Condition |
|-----------|-----------|
|-----------|-----------|

| | |
|---------------------------------|---|
| System.OverflowException | The <code>System.TimeSpan</code> represented by <i>value</i> is greater than <code>System.TimeSpan.MaxValue</code> or less than <code>System.TimeSpan.MinValue</code> . |
| System.ArgumentException | <i>value</i> is equal to <code>System.Double.NaN</code> . |

1
2
3

The following member must be implemented if the ExtendedNumerics library is present in the implementation.

TimeSpan.FromMinutes(System.Double) Method

```
[ILAsm]  
.method public hidebysig static valuetype System.TimeSpan  
FromMinutes(float64 value)  
  
[C#]  
public static TimeSpan FromMinutes(double value)
```

Summary

Returns a `System.TimeSpan` that represents the specified number of minutes where the specification is accurate to the nearest millisecond.

Parameters

| Parameter | Description |
|--------------|---|
| <i>value</i> | A <code>System.Double</code> that specifies the number of minutes with which the new <code>System.TimeSpan</code> is initialized. |

Return Value

A `System.TimeSpan` that represents *value*.

Description

value will only be considered accurate to the nearest millisecond.

If *value* is `System.Double.PositiveInfinity`, a `System.TimeSpan` with the value `System.TimeSpan.MaxValue` is returned. If *value* is `System.Double.NegativeInfinity`, a `System.TimeSpan` with the value `System.TimeSpan.MinValue` is returned.

Exceptions

| Exception | Condition |
|-----------|-----------|
|-----------|-----------|

| | |
|---------------------------------|---|
| System.OverflowException | The <code>System.TimeSpan</code> represented by <i>value</i> is greater than <code>System.TimeSpan.MaxValue</code> or less than <code>System.TimeSpan.MinValue</code> . |
| System.ArgumentException | <i>value</i> is equal to <code>System.Double.NaN</code> . |

1
2
3

The following member must be implemented if the ExtendedNumerics library is present in the implementation.

TimeSpan.FromSeconds(System.Double) Method

```
[ILAsm]  
.method public hidebysig static valuetype System.TimeSpan  
FromSeconds(float64 value)  
  
[C#]  
public static TimeSpan FromSeconds(double value)
```

Summary

Returns a `System.TimeSpan` that represents the specified number of seconds where the specification is accurate to the nearest millisecond.

Parameters

| Parameter | Description |
|--------------|---|
| <i>value</i> | A <code>System.Double</code> that specifies the number of seconds with which the new <code>System.TimeSpan</code> is initialized. |

Return Value

A `System.TimeSpan` that represents *value*.

Description

value will only be considered accurate to the nearest millisecond.

If *value* is `System.Double.PositiveInfinity`, a `System.TimeSpan` with the value `System.TimeSpan.MaxValue` is returned. If *value* is `System.Double.NegativeInfinity`, a `System.TimeSpan` with the value `System.TimeSpan.MinValue` is returned.

Exceptions

| Exception | Condition |
|-----------|-----------|
|-----------|-----------|

| | |
|---------------------------------|---|
| System.OverflowException | The <code>System.TimeSpan</code> represented by <i>value</i> is greater than <code>System.TimeSpan.MaxValue</code> or less than <code>System.TimeSpan.MinValue</code> . |
| System.ArgumentException | <i>value</i> is equal to <code>System.Double.NaN</code> . |

1
2
3

1 TimeSpan.FromTicks(System.Int64) Method

```
2 [ILAsm]  
3 .method public hidebysig static valuetype System.TimeSpan FromTicks(int64  
4 value)  
  
5 [C#]  
6 public static TimeSpan FromTicks(long value)
```

7 Summary

8 Returns a System.TimeSpan that represents the specified number of ticks.

9 Parameters

| Parameter | Description |
|--------------|--|
| <i>value</i> | A System.Int64 that specifies the number of ticks with which the new System.TimeSpan is initialized. |

13 Return Value

15 A System.TimeSpan with a value of *value*.

16 Description

17 This method is equivalent to the System.TimeSpan(System.Int64) constructor.

1 TimeSpan.GetHashCode() Method

```
2 [ILAsm]  
3 .method public hidebysig virtual int32 GetHashCode()  
4 [C#]  
5 public override int GetHashCode()
```

6 Summary

7 Generates a hash code for the current instance.

8 Return Value

9
10 A `System.Int32` value containing a hash code for the current instance.

11 Description

12 The algorithm used to generate the hash code is unspecified.

13
14 [*Note:* This method overrides `System.Object.GetHashCode()`.]
15
16
17

1 TimeSpan.Negate() Method

```
2 [ILAsm]
3 .method public hidebysig instance valuetype System.TimeSpan Negate()
4 [C#]
5 public TimeSpan Negate()
```

6 Summary

7 Returns a System.TimeSpan with the same absolute value but opposite sign as the
8 current instance.

9 Return Value

10
11 A System.TimeSpan with the same absolute value but with the opposite sign as the
12 current instance.

13 Exceptions

| Exception | Condition |
|--------------------------|--|
| System.OverflowException | The value of the current instance is System.TimeSpan.MinValue. |

1 TimeSpan.op_Addition(System.TimeSpan, 2 System.TimeSpan) Method

```
3 [ILAsm]  
4 .method public hidebysig static specialname valuetype System.TimeSpan  
5 op_Addition(valuetype System.TimeSpan t1, valuetype System.TimeSpan t2)  
  
6 [C#]  
7 public static TimeSpan operator +(TimeSpan t1, TimeSpan t2)
```

8 Summary

9 Adds the values of two System.TimeSpan instances.

10 Parameters

| Parameter | Description |
|-----------|-----------------------------|
| <i>t1</i> | The first System.TimeSpan. |
| <i>t2</i> | The second System.TimeSpan. |

13 Return Value

14 A System.TimeSpan whose value is the sum of the values of *t1* and *t2*.

17 Exceptions

| Exception | Condition |
|---------------------------------|--|
| System.OverflowException | The sum of <i>t1</i> and <i>t2</i> is less than System.TimeSpan.MinValue or greater than System.TimeSpan.MaxValue. |

1 TimeSpan.op_Equality(System.TimeSpan, 2 System.TimeSpan) Method

```
3 [ILAsm]  
4 .method public hidebysig static specialname bool op_Equality(valuetype  
5 System.TimeSpan t1, valuetype System.TimeSpan t2)  
  
6 [C#]  
7 public static bool operator ==(TimeSpan t1, TimeSpan t2)
```

8 Summary

9 Determines whether the value of one System.TimeSpan is equal to the value of another
10 System.TimeSpan.

11 Parameters

| Parameter | Description |
|-----------|----------------------------|
| <i>t1</i> | The first System.TimeSpan |
| <i>t2</i> | The second System.TimeSpan |

14 Return Value

15 true if the values of *t1* and *t2* are equal; otherwise, false.
16
17
18

1 TimeSpan.op_GreaterThan(System.TimeSpan, 2 System.TimeSpan) Method 3

```
4    [ILAsm]  
5    .method public hidebysig static specialname bool op_GreaterThan(valuetype  
6    System.TimeSpan t1, valuetype System.TimeSpan t2)  
  
7    [C#]  
8    public static bool operator >(TimeSpan t1, TimeSpan t2)
```

9 Summary

10 Determines whether the value one `System.TimeSpan` is greater than the value of
11 another `System.TimeSpan`.

12 Parameters

| Parameter | Description |
|-----------|---|
| <i>t1</i> | The first <code>System.TimeSpan</code> . |
| <i>t2</i> | The second <code>System.TimeSpan</code> . |

15 Return Value

16 `true` if the value of *t1* is greater than the value of *t2*; otherwise, `false`.
17
18
19

1 TimeSpan.op_GreaterThanOrEqual(System.TimeSpan, System.TimeSpan) Method

```
4    [ILAsm]  
5    .method public hidebysig static specialname bool  
6    op_GreaterThanOrEqual(valuetype System.TimeSpan t1, valuetype  
7    System.TimeSpan t2)  
  
8    [C#]  
9    public static bool operator >=(TimeSpan t1, TimeSpan t2)
```

10 Summary

11 Determines whether the value of one System.TimeSpan is greater than or equal to the
12 value of another System.TimeSpan.

13 Parameters

| Parameter | Description |
|-----------|-----------------------------|
| <i>t1</i> | The first System.TimeSpan. |
| <i>t2</i> | The second System.TimeSpan. |

16 Return Value

17 true if the value of *t1* is greater than or equal to the value of *t2*; otherwise, false.
18
19
20

1 TimeSpan.op_Inequality(System.TimeSpan, System.TimeSpan) Method

```
3 [ILAsm]  
4 .method public hidebysig static specialname bool op_Inequality(valuetype  
5 System.TimeSpan t1, valuetype System.TimeSpan t2)  
  
6 [C#]  
7 public static bool operator !=(TimeSpan t1, TimeSpan t2)
```

8 Summary

9 Determines whether the value of one System.TimeSpan is unequal to the value of
10 another System.TimeSpan.

11 Parameters

| Parameter | Description |
|-----------|-----------------------------|
| <i>t1</i> | The first System.TimeSpan. |
| <i>t2</i> | The second System.TimeSpan. |

14 Return Value

15 true if the values of *t1* and *t2* are unequal; otherwise, false.
16
17
18

1 TimeSpan.op_LessThan(System.TimeSpan, 2 System.TimeSpan) Method

```
3 [ILAsm]  
4 .method public hidebysig static specialname bool op_LessThan(valuetype  
5 System.TimeSpan t1, valuetype System.TimeSpan t2)  
  
6 [C#]  
7 public static bool operator <(TimeSpan t1, TimeSpan t2)
```

8 Summary

9 Determines whether the value of one System.TimeSpan is less than the value of another
10 System.TimeSpan.

11 Parameters

| Parameter | Description |
|-----------|-----------------------------|
| <i>t1</i> | The first System.TimeSpan. |
| <i>t2</i> | The second System.TimeSpan. |

14 Return Value

15 true if the value of *t1* is less than the value of *t2*; otherwise, false.
16
17
18

1 TimeSpan.op_LessThanOrEqual(System.TimeSpan, System.TimeSpan) Method

```
4    [ILAsm]  
5    .method public hidebysig static specialname bool  
6    op_LessThanOrEqual(valuetype System.TimeSpan t1, valuetype System.TimeSpan  
7    t2)  
  
8    [C#]  
9    public static bool operator <=(TimeSpan t1, TimeSpan t2)
```

10 Summary

11 Determines whether the value of one System.TimeSpan is less than or equal to the
12 value of another System.TimeSpan.

13 Parameters

| Parameter | Description |
|-----------|-----------------------------|
| <i>t1</i> | The first System.TimeSpan. |
| <i>t2</i> | The second System.TimeSpan. |

16 Return Value

17 true if the value of *t1* is less than or equal to the value of *t2*; otherwise, false.
18
19
20

1 TimeSpan.op_Subtraction(System.TimeSpan, System.TimeSpan) Method

```
3 [ILAsm]
4 .method public hidebysig static specialname valuetype System.TimeSpan
5 op_Subtraction(valuetype System.TimeSpan t1, valuetype System.TimeSpan t2)
6
7 [C#]
8 public static TimeSpan operator -(TimeSpan t1, TimeSpan t2)
```

8 Summary

9 Subtracts the value of one System.TimeSpan from the value of another
10 System.TimeSpan.

11 Parameters

| Parameter | Description |
|-----------|-----------------------------|
| <i>t1</i> | The first System.TimeSpan. |
| <i>t2</i> | The second System.TimeSpan. |

15 Return Value

17 A System.TimeSpan whose value is the result of the value of *t1* minus the value of *t2*.

18 Exceptions

| Exception | Condition |
|---------------------------------|--|
| System.OverflowException | The value of <i>t2</i> subtracted from <i>t1</i> is less than System.TimeSpan.MinValue or greater than System.TimeSpan.MaxValue. |

1 TimeSpan.op_UnaryNegation(System.TimeSpan) Method

```
4    [ILAsm]  
5    .method public hidebysig static specialname valuetype System.TimeSpan  
6    op_UnaryNegation(valuetype System.TimeSpan t)  
  
7    [C#]  
8    public static TimeSpan operator -(TimeSpan t)
```

9 Summary

10 Returns a System.TimeSpan whose value is the negated value of a specified
11 System.TimeSpan.

12 Parameters

| Parameter | Description |
|-----------|--|
| <i>t</i> | A System.TimeSpan whose value will be negated. |

16 Return Value

18 A System.TimeSpan with the same absolute value but the opposite sign as *t*.

19 Exceptions

| Exception | Condition |
|---------------------------------|---|
| System.OverflowException | <i>t</i> equals System.TimeSpan.MinValue. |

1 TimeSpan.op_UnaryPlus(System.TimeSpan)

2 Method

```
3 [ILAsm]  
4 .method public hidebysig static specialname valuetype System.TimeSpan  
5 op_UnaryPlus(valuetype System.TimeSpan t)  
  
6 [C#]  
7 public static TimeSpan operator +(TimeSpan t)
```

8 Summary

9 Returns the specified instance of System.TimeSpan.

10 Parameters

| Parameter | Description |
|-----------|--------------------|
| <i>t</i> | A System.TimeSpan. |

13 Return Value

14 System.TimeSpan*t*.

15 Description

16 This method returns System.TimeSpan*t*.

1 TimeSpan.Parse(System.String) Method

```
2 [ILAsm]  
3 .method public hidebysig static valuetype System.TimeSpan Parse(string s)  
4 [C#]  
5 public static TimeSpan Parse(string s)
```

6 Summary

7 Returns the specified System.String converted to a System.TimeSpan value.

8 Parameters

| Parameter | Description |
|-----------|---|
| s | <p>A System.String containing the value to convert. s contains a time interval in the following form:</p> <p>[ws][-][d.]hh:mm:ss[.ff][ws]</p> <p>Items in square brackets ('[' and ']') are optional. Colons and periods (':' and '.') are literal characters. For details on the remaining symbols, see the description section.</p> |

12 Return Value

14 The System.TimeSpan value obtained from s.

15 Description

16 The symbols used in the parameter description for s are as follows:

| Item | Description |
|------|---|
| ws | White space (zero or more space and/or tab characters). |
| "-" | Minus sign, indicating a negative time interval. |
| "d" | Days. |

| | |
|------|---|
| "hh" | Hours, ranging from 0 to 23 inclusive. |
| "mm" | Minutes, ranging from 0 to 59 inclusive. |
| "ss" | Seconds, ranging from 0 to 59 inclusive. |
| "ff" | Fractional seconds, from 1 to 7 decimal digits inclusive. |

Exceptions

| Exception | Condition |
|-------------------------------------|--|
| System.ArgumentNullException | s is a null reference. |
| System.FormatException | s is in an invalid format. |
| System.OverflowException | s represents a number greater than <code>System.TimeSpan.MaxValue</code> or less than <code>System.TimeSpan.MinValue</code> . -or- At least one of the hours, minutes, or seconds components is outside its valid range. |

Example

This example demonstrates parsing a string to obtain a `System.TimeSpan`.

[C#]

```
using System;
public class TimeSpanParseExample {
    public static void Main() {
        String str = "-5.12:34:56.789";
        TimeSpan ts = TimeSpan.Parse(str);
        Console.WriteLine(@"The string "{0}"", str);
        Console.WriteLine("parses to TimeSpan {0}", ts);
    }
}
```

```
1
2 The output is
3
4 The string "      -5.12:34:56.789      "
5 parses to TimeSpan -5.12:34:56.7890000
6
7
```

1 TimeSpan.Subtract(System.TimeSpan)

2 Method

```
3 [ILAsm]  
4 .method public hidebysig instance valuetype System.TimeSpan  
5 Subtract(valuetype System.TimeSpan ts)  
  
6 [C#]  
7 public TimeSpan Subtract(TimeSpan ts)
```

8 Summary

9 Subtracts the value of the specified `System.TimeSpan` from the value of the current
10 instance.

11 Parameters

| Parameter | Description |
|-----------|--|
| <i>ts</i> | A <code>System.TimeSpan</code> whose value to subtract from the value of the current instance. |

15 Return Value

17 A `System.TimeSpan` whose value is equal to the value of the current instance minus the
18 value of *ts*.

19 Exceptions

| Exception | Condition |
|---------------------------------|---|
| System.OverflowException | The difference between the value of the current instance and <i>ts</i> is less than <code>System.TimeSpan.MinValue</code> or greater than <code>System.TimeSpan.MaxValue</code> . |

1 TimeSpan.ToString() Method

```
2 [ILAsm]  
3 .method public hidebysig virtual string ToString()  
  
4 [C#]  
5 public override string ToString()
```

6 Summary

7 Returns a `System.String` representation of the value of the current instance.

8 Return Value

10 A `System.String` representation of the current instance formatted as follows:

12 [-][d.]hh:mm:ss[.ff]

14 Items in square brackets ('[' and ']') are included provisionally: '-' is included if and only
15 if the current instance is negative; "d." and ".ff" are included if and only if those
16 components are non-zero. Colons and periods (':' and '.') are literal characters. Other
17 components are as follows.

| Component | Description |
|-----------|--|
| "_" | Minus sign, indicating a negative time interval. |
| "d" | Days. |
| "hh" | Hours, ranging from 0 to 23 inclusive. |
| "mm" | Minutes, ranging from 0 to 59 inclusive. |
| "ss" | Seconds, ranging from 0 to 59 inclusive. |
| "ff" | Fractional seconds. |

19 Description

20 [Note: This method overrides `System.Object.ToString`.]
21
22

1 Example

3 This example demonstrates the `System.TimeSpan.ToString` method.

5 [C#]

```
6 using System;
7 public class TimeSpanToStringExample {
8     public static void Main() {
9         TimeSpan tsOne = new TimeSpan(1, 23, 45, 54, 321);
10        TimeSpan tsTwo = new TimeSpan(0, 23, 45, 54, 0);
11        Console.Write("TimeSpan one, with d. and.ff: ");
12        Console.WriteLine("{0}", tsOne.ToString());
13        Console.Write("TimeSpan two, without d. and.ff: ");
14        Console.WriteLine("{0}", tsTwo.ToString());
15    }
16 }
```

17 The output is

18 TimeSpan one, with d. and.ff: 1.23:45:54.3210000

22 TimeSpan two, without d. and.ff: 23:45:54

1 TimeSpan.Days Property

```
2 [ILAsm]  
3 .property int32 Days { public hidebysig specialname instance int32  
4 get_Days() }  
  
5 [C#]  
6 public int Days { get; }
```

7 Summary

8 Gets the number days represented by the current instance.

9 Property Value

11 A System.Int32 represents the days component of the current instance. [*Note:* See
12 System.TimeSpan.ToString for a more detailed description of the days component.]
13
14

15 Description

16 This property is read-only.

17 Example

19 This example demonstrates using the System.TimeSpan.Days property.

```
20 [C#]  
21  
22 using System;  
23 public class TimeSpanPropertiesExampleOne {  
24     public static void Main() {  
25         TimeSpan ts = new TimeSpan((Int64)10e12+3456789);  
26         Console.WriteLine(ts.ToString());  
27         Console.WriteLine("Days: {0}", ts.Days );  
28     }  
29 }
```

30 The output is

31 11.13:46:40.3456789
32
33
34

35 Days: 11
36
37

1 TimeSpan.Hours Property

```
2 [ILAsm]  
3 .property int32 Hours { public hidebysig specialname instance int32  
4 get_Hours() }
```

```
5 [C#]  
6 public int Hours { get; }
```

7 Summary

8 Gets the number of hours represented by the current instance.

9 Property Value

10
11 A `System.Int32` between 0 and 23 inclusive, that represents the hours component of
12 the current instance. [*Note:* See `System.TimeSpan.ToString` for a more detailed
13 description of the hours component.]
14
15

16 Description

17 This property is read-only.

18 Example

19
20 This example demonstrates using the `System.TimeSpan.Hours` property.

```
21 [C#]  
22  
23 using System;  
24 public class TimeSpanPropertiesExampleOne {  
25     public static void Main() {  
26         TimeSpan ts = new TimeSpan((Int64)10e12+3456789);  
27         Console.WriteLine(ts.ToString());  
28         Console.WriteLine("Hours: {0}", ts.Hours );  
29     }  
30 }
```

31 The output is

32
33 11.13:46:40.3456789
34

35
36 Hours: 13
37
38

1 TimeSpan.Milliseconds Property

```
2 [ILAsm]  
3 .property int32 Milliseconds { public hidebysig specialname instance int32  
4 get_Milliseconds() }  
  
5 [C#]  
6 public int Milliseconds { get; }
```

7 Summary

8 Gets the number of milliseconds represented by the current instance.

9 Property Value

10
11 A `System.Int32` between 0 and 999 inclusive, that represents the fractional seconds
12 component of the current instance converted to milliseconds. [*Note:* See
13 `System.TimeSpan.ToString` for a more detailed description of the fractional seconds
14 component.]
15
16

17 Description

18 This property is read-only.

19 Example

20
21 This example demonstrates using the `System.TimeSpan.Milliseconds` property.

```
22 [C#]  
23  
24 using System;  
25 public class TimeSpanPropertiesExampleOne {  
26     public static void Main() {  
27         TimeSpan ts = new TimeSpan((Int64)10e12+3456789);  
28         Console.WriteLine(ts.ToString());  
29         Console.WriteLine("Milliseconds: {0}", ts.Milliseconds );  
30     }  
31 }
```

32 The output is

33
34 11.13:46:40.3456789

35
36
37 Milliseconds: 345
38
39

1 TimeSpan.Minutes Property

```
2 [ILAsm]  
3 .property int32 Minutes { public hidebysig specialname instance int32  
4 get_Minutes() }
```

```
5 [C#]  
6 public int Minutes { get; }
```

7 Summary

8 Gets the number of minutes represented by the current instance.

9 Property Value

10
11 A `System.Int32` between 0 and 59 inclusive, that represents the minutes component of
12 the current instance. [*Note:* See `System.TimeSpan.ToString` for a more detailed
13 description of the minutes component.]
14
15

16 Description

17 This property is read-only.

18 Example

19
20 This example demonstrates using the `System.TimeSpan.Minutes` property.

```
21 [C#]  
22  
23 using System;  
24 public class TimeSpanPropertiesExampleOne {  
25     public static void Main() {  
26         TimeSpan ts = new TimeSpan((Int64)10e12+3456789);  
27         Console.WriteLine(ts.ToString());  
28         Console.WriteLine("Minutes: {0}", ts.Minutes );  
29     }  
30 }
```

31 The output is

32
33 11.13:46:40.3456789
34

35
36 Minutes: 46
37
38

1 TimeSpan.Seconds Property

```
2 [ILAsm]  
3 .property int32 Seconds { public hidebysig specialname instance int32  
4 get_Seconds() }
```

```
5 [C#]  
6 public int Seconds { get; }
```

7 Summary

8 Gets the number of seconds represented by the current instance.

9 Property Value

10
11 A `System.Int32` between 0 and 59 inclusive, that represents the seconds component of
12 the current instance. [*Note:* See `System.TimeSpan.ToString` for a more detailed
13 description of the seconds component.]
14
15

16 Description

17 This property is read-only.

18 Example

19
20 This example demonstrates using the `System.TimeSpan.Seconds` property.

```
21 [C#]  
22  
23 using System;  
24 public class TimeSpanPropertiesExampleOne {  
25     public static void Main() {  
26         TimeSpan ts = new TimeSpan((Int64)10e12+3456789);  
27         Console.WriteLine(ts.ToString());  
28         Console.WriteLine("Seconds: {0}", ts.Seconds );  
29     }  
30 }
```

31 The output is

32
33 11.13:46:40.3456789
34

35
36 Seconds: 40
37
38

1 TimeSpan.Ticks Property

```
2 [ILAsm]  
3 .property int64 Ticks { public hidebysig specialname instance int64  
4 get_Ticks() }  
  
5 [C#]  
6 public long Ticks { get; }
```

7 Summary

8 Gets the number of ticks represented by the current instance.

9 Property Value

10
11 A `System.Int64` specifying the number of ticks represented by the current instance.

12 Description

13 This property is read-only.
14

The following member must be implemented if the ExtendedNumerics library is present in the implementation.

TimeSpan.TotalDays Property

```
[ILAsm]
.property float64 TotalDays { public hidebysig specialname instance
float64 get_TotalDays() }

[C#]
public double TotalDays { get; }
```

Summary

Gets the value of the current instance expressed in days.

Property Value

A `System.Double` that specifies the total number of days represented by the current instance.

Description

This property is read-only.

[*Note:* This property converts the value of the current instance from ticks to days. This number can include whole and fractional days.]

Example

This example demonstrates using the `System.TimeSpan.TotalDays` property.

```
[C#]
using System;
public class TimeSpanTotalUnitsProperties{
    public static void Main() {
        TimeSpan ts = new TimeSpan((Int64)10e12);
        Console.WriteLine(ts.ToString());
        Console.WriteLine("TotalDays: {0}", ts.TotalDays);
    }
}
```

The output is

11.13:46:40

1 TotalDays: 11.5740740740741

2

3

The following member must be implemented if the ExtendedNumerics library is present in the implementation.

TimeSpan.TotalHours Property

```
[ILAsm]
.property float64 TotalHours { public hidebysig specialname instance
float64 get_TotalHours() }

[C#]
public double TotalHours { get; }
```

Summary

Gets the value of the current instance expressed in hours.

Property Value

A `System.Double` that specifies the total number of hours represented by the current instance.

Description

This property is read-only.

[*Note:* This property converts the value of the current instance from ticks to hours. This number can include whole and fractional hours.]

Example

This example demonstrates using the `System.TimeSpan.TotalHours` property.

```
[C#]
using System;
public class TimeSpanTotalUnitsProperties{
    public static void Main() {
        TimeSpan ts = new TimeSpan((Int64)10e12);
        Console.WriteLine(ts.ToString());
        Console.WriteLine("TotalHours: {0}", ts.TotalHours);
    }
}
```

The output is

11.13:46:40

1 TotalHours: 277.777777777778

2

3

The following member must be implemented if the ExtendedNumerics library is present in the implementation.

TimeSpan.TotalMilliseconds Property

```
[ILAsm]  
.property float64 TotalMilliseconds { public hidebysig specialname  
instance float64 get_TotalMilliseconds() }  
  
[C#]  
public double TotalMilliseconds { get; }
```

Summary

Gets the value of the current instance expressed in milliseconds.

Property Value

A `System.Double` that specifies the total number of milliseconds represented by the current instance.

Description

This property is read-only.

[*Note:* This property converts the value of the current instance from ticks to milliseconds. This number can include whole and fractional milliseconds.]

Example

This example demonstrates using the `System.TimeSpan.TotalMilliseconds` property.

```
[C#]  
  
using System;  
public class TimeSpanTotalUnitsProperties{  
    public static void Main() {  
        TimeSpan ts = new TimeSpan((Int64)10e12);  
        Console.WriteLine(ts.ToString());  
        Console.WriteLine("TotalMilliseconds: {0}", ts.TotalMilliseconds);  
    }  
}
```

The output is

11.13:46:40

```
1  TotalMilliseconds: 1000000000
2
3
```

The following member must be implemented if the ExtendedNumerics library is present in the implementation.

TimeSpan.TotalMinutes Property

```
[ILAsm]
.property float64 TotalMinutes { public hideby sig specialname instance
float64 get_TotalMinutes() }

[C#]
public double TotalMinutes { get; }
```

Summary

Gets the value of the current instance expressed in minutes.

Property Value

A `System.Double` that specifies the total number of minutes represented by the current instance.

Description

This property is read-only.

[*Note:* This property converts the value of the current instance from ticks to minutes. This number can include whole and fractional minutes.]

Example

This example demonstrates using the `System.TimeSpan.TotalMinutes` property.

```
[C#]
using System;
public class TimeSpanTotalUnitsProperties{
    public static void Main() {
        TimeSpan ts = new TimeSpan((Int64)10e12);
        Console.WriteLine(ts.ToString());
        Console.WriteLine("TotalMinutes: {0}", ts.TotalMinutes);
    }
}
```

The output is

11.13:46:40

1 TotalMinutes: 16666.66666666667

2

3

The following member must be implemented if the ExtendedNumerics library is present in the implementation.

TimeSpan.TotalSeconds Property

```
[ILAsm]
.property float64 TotalSeconds { public hidebysig specialname instance
float64 get_TotalSeconds() }

[C#]
public double TotalSeconds { get; }
```

Summary

Gets the value of the current instance expressed in seconds.

Property Value

A `System.Double` that specifies the total number of seconds represented by the current instance.

Description

This property is read-only.

[*Note:* This property converts the value of the current instance from ticks to seconds. This number can include whole and fractional seconds.]

Example

This example demonstrates using the `System.TimeSpan.TotalSeconds` property.

```
[C#]
using System;
public class TimeSpanTotalUnitsProperties{
    public static void Main() {
        TimeSpan ts = new TimeSpan((Int64)10e12);
        Console.WriteLine(ts.ToString());
        Console.WriteLine("TotalSeconds: {0}", ts.TotalSeconds);
    }
}
```

The output is

11.13:46:40

1 TotalSeconds:1000000

2

3