

System.Char Structure

```
[ILAsm]
.class public sequential sealed serializable Char extends System.ValueType
implements System.IComparable, System.IComparable`1<char>,
System.IEquatable`1<char>

[C#]
public struct Char: IComparable, IComparable<Char>, IEquatable<Char>
```

Assembly Info:

- *Name:* mscorlib
- *Public Key:* [00 00 00 00 00 00 00 00 04 00 00 00 00 00 00 00]
- *Version:* 2.0.x.x
- *Attributes:*
 - CLSCompliantAttribute(true)

Implements:

- **System.IComparable**
- **System.IComparable<System.Char>**
- **System.IEquatable<System.Char>**

Summary

Represents a Unicode character.

Inherits From: System.ValueType

Library: BCL

Thread Safety: This type is safe for multithreaded operations.

Description

The `System.Char` value type represents Unicode characters, with code points ranging from 0 to 65,535.

[*Note:* The *code point* of a Unicode character is that character's 2-byte, encoded value.]

[*Note:* The `System.Globalization.UnicodeCategory` enumeration describes the categories that a Unicode character can be mapped to. For information on mapping specific Unicode characters to Unicode categories, see the `UnicodeData.txt` file in the Unicode Character Database at

1 <http://www.unicode.org/Public/UNIDATA/UnicodeCharacterDatabase.html>. The
2 UnicodeData.txt file format is described at [http://www.unicode.org/Public/3.1-
4 Update/UnicodeData-3.1.0.html](http://www.unicode.org/Public/3.1-
3 Update/UnicodeData-3.1.0.html).]
5
6

Char.MaxValue Field

```
[ILAsm]  
.field public static literal valuetype System.Char MaxValue = (char)0xFFFF  
  
[C#]  
public const char MaxValue = (char)0xFFFF
```

Summary

Contains the maximum code point for the `System.Char` type.

Description

The numeric value of this constant is 65,535.

Char.MinValue Field

```
[ILAsm]  
.field public static literal valuetype System.Char MinValue = (char)0x0  
  
[C#]  
public const char MinValue = (char)0x0
```

Summary

Contains the minimum code point for the `System.Char` type.

Description

The numeric value of this constant is 0.

Char.CompareTo(System.Char) Method

```
[ILAsm]  
.method public final hidebysig virtual int32 CompareTo(char value)  
  
[C#]  
public int CompareTo(char value)
```

Summary

Returns the sort order of the current instance compared to the specified `System.Char`.

Parameters

Parameter	Description
<i>value</i>	The <code>System.Char</code> to compare to the current instance.

Return Value

The return value is a negative number, zero, or a positive number reflecting the sort order of the current instance as compared to *value*. For non-zero return values, the exact value returned by this method is unspecified. The following table defines the return value:

Return Value	Description
A negative number	Current instance < <i>value</i> .
Zero	Current instance == <i>value</i> .
A positive number	Current instance > <i>value</i> .

Description

The comparison performed by this method is based on the code points of the current instance and *value*, not necessarily their lexicographical characteristics.

[*Note:* This method is implemented to support the `System.IComparable<Char>` interface.]

1
2
3

Char.CompareTo(System.Object) Method

```
[ILAsm]  
.method public final hidebysig virtual int32 CompareTo(object value)  
  
[C#]  
public int CompareTo(object value)
```

Summary

Returns the sort order of the current instance compared to the specified `System.Object`.

Parameters

Parameter	Description
<i>value</i>	The <code>System.Object</code> to compare to the current instance.

Return Value

The return value is a negative number, zero, or a positive number reflecting the sort order of the current instance as compared to *value*. For non-zero return values, the exact value returned by this method is unspecified. The following table defines the return value:

Return Value	Description
A negative number	Current instance < <i>value</i> .
Zero	Current instance == <i>value</i> .
A positive number	Current instance > <i>value</i> , or <i>value</i> is a null reference.

Description

The comparison performed by this method is based on the code points of the current instance and *value*, not necessarily their lexicographical characteristics.

[*Note:* This method is implemented to support the `System.IComparable` interface.]

1
2

3 **Exceptions**

4
5

Exception	Condition
System.ArgumentException	<i>value</i> is not a <code>System.Char</code> and is not a null reference.

6
7
8

Char.Equals(System.Char) Method

```
[ILAsm]  
.method public hidebysig virtual bool Equals(char obj)  
  
[C#]  
public override bool Equals(char obj)
```

Summary

Determines whether the current instance and the specified `System.Char` represent the same value.

Parameters

Parameter	Description
<i>obj</i>	The <code>System.Char</code> to compare to the current instance.

Return Value

`true` if *obj* represents the same value as the current instance; otherwise, `false`.

Description

The comparison performed by this method is based on the code points of the current instance and *obj*, not necessarily their lexicographical characteristics.

[*Note:* This method is implemented to support the `System.IEquatable<Char>` interface.]

Char.Equals(System.Object) Method

```
[ILAsm]  
.method public hidebysig virtual bool Equals(object obj)  
  
[C#]  
public override bool Equals(object obj)
```

Summary

Determines whether the current instance and the specified `System.Object` represent the same type and value.

Parameters

Parameter	Description
<i>obj</i>	The <code>System.Object</code> to compare to the current instance.

Return Value

`true` if *obj* represents the same type and value as the current instance. If *obj* is a null reference or is not an instance of `System.Char`, returns `false`.

Description

The comparison performed by this method is based on the code points of the current instance and *obj*, not necessarily their lexicographical characteristics.

[*Note:* This method overrides `System.Object.Equals`.]

Char.GetHashCode() Method

```
[ILAsm]  
.method public hidebysig virtual int32 GetHashCode()  
  
[C#]  
public override int GetHashCode()
```

Summary

Generates a hash code for the current instance.

Return Value

A `System.Int32` value containing a hash code for the current instance.

Description

The algorithm used to generate the hash code is unspecified.

[*Note:* This method overrides `System.Object.GetHashCode()`.]

The following member must be implemented if the ExtendedNumerics library is present in the implementation.

Char.GetNumericValue(System.String, System.Int32) Method

```
[ILAsm]  
.method public hidebysig static float64 GetNumericValue(string s, int32  
index)  
  
[C#]  
public static double GetNumericValue(string s, int index)
```

Summary

Returns the numeric value associated with the Unicode character at the specified position in the specified `System.String`.

Parameters

Parameter	Description
<i>s</i>	A <code>System.String</code> .
<i>index</i>	A <code>System.Int32</code> that specifies the position of a character in <i>s</i> .

Return Value

A `System.Double` representing the numeric value associated with the `System.Char` at position *index* in *s* if and only if that `System.Char` has an associated numeric value; otherwise, -1.0.

Description

A character has an associated numeric value if and only if it is a member of one of the following categories in `System.Globalization.UnicodeCategory`:
`System.Globalization.UnicodeCategory.DecimalDigitNumber`,
`System.Globalization.UnicodeCategory.LetterNumber`, or
`System.Globalization.UnicodeCategory.OtherNumber`.

Exceptions

Exception	Condition
System.ArgumentNullException	s is a null reference.
System.ArgumentOutOfRangeException	The value of <i>index</i> is less than zero, or greater than or equal to the length of s.

1
2
3

The following member must be implemented if the ExtendedNumerics library is present in the implementation.

Char.GetNumericValue(System.Char) Method

```
[ILAsm]
.method public hidebysig static float64 GetNumericValue(valuetype
System.Char c)

[C#]
public static double GetNumericValue(char c)
```

Summary

Returns the numeric value associated with the specified Unicode character.

Parameters

Parameter	Description
<i>c</i>	A Unicode character.

Return Value

A `System.Double` representing the numeric value associated with *c* if and only if *c* has an associated numeric value; otherwise, -1.0.

Description

A character has an associated numeric value if and only if it is a member of one of the following categories in `System.Globalization.UnicodeCategory`:
`System.Globalization.UnicodeCategory.DecimalDigitNumber`,
`System.Globalization.UnicodeCategory.LetterNumber`, or
`System.Globalization.UnicodeCategory.OtherNumber`.

Example

The following example demonstrates the `System.Char.GetNumericValue` method.

```
[C#]

using System;
public class GetNumericValueExample {
public static void Main() {
```

```
1 Char[] cAry = {'8', 'V', Convert.ToChar(0X00BC)};
2 //Unicode U+00BC is the code point for the character
3 //representation of 1/4
4 foreach(Char c in cAry) {
5     Console.Write("Numeric value of Unicode " +
6         "character {0} ", c);
7     Console.WriteLine(" is {0}",
8         Char.GetNumericValue(c));
9 }
10 }
11 }
12 The output is
13
14 Numeric value of Unicode character 8 is 8
15
16
17 Numeric value of Unicode character V is -1
18
19
20 Numeric value of Unicode character 1/4 is 0.25
21
22
```

Char.GetUnicodeCategory(System.String, System.Int32) Method

```
[ILAsm]  
.method public hidebysig static valuetype  
System.Globalization.UnicodeCategory GetUnicodeCategory(string s, int32  
index)  
  
[C#]  
public static UnicodeCategory GetUnicodeCategory(string s, int index)
```

Summary

Determines the `System.Globalization.UnicodeCategory` of the character at the specified position in the specified `System.String`.

Parameters

Parameter	Description
<i>s</i>	A <code>System.String</code> .
<i>index</i>	A <code>System.Int32</code> that specifies the position of a character in <i>s</i> .

Return Value

The `System.Globalization.UnicodeCategory` of the `System.Char` at position *index* in *s*.

Description

[*Note:* For more information regarding Unicode categories, see `System.Globalization.UnicodeCategory`.]

Exceptions

Exception	Condition
-----------	-----------

System.ArgumentNullException	s is a null reference.
System.ArgumentOutOfRangeException	The value of <i>index</i> is less than zero, or greater than or equal to the length of s.

1
2
3

Char.GetUnicodeCategory(System.Char)

Method

```
[ILAsm]  
.method public hidebysig static valuetype  
System.Globalization.UnicodeCategory GetUnicodeCategory(valuetype  
System.Char c)  
  
[C#]  
public static UnicodeCategory GetUnicodeCategory(char c)
```

Summary

Determines the `System.Globalization.UnicodeCategory` of the specified Unicode character.

Parameters

Parameter	Description
<i>c</i>	A Unicode character.

Return Value

The `System.Globalization.UnicodeCategory` of *c*.

Description

[*Note:* For more information regarding Unicode categories, see `System.Globalization.UnicodeCategory`.]

Char.IsControl(System.String, System.Int32)

Method

```
[ILAsm]  
.method public hidebysig static bool IsControl(string s, int32 index)  
  
[C#]  
public static bool IsControl(string s, int index)
```

Summary

Determines whether the character at the specified position in the specified `System.String` is a control character.

Parameters

Parameter	Description
<code>s</code>	A <code>System.String</code> .
<code>index</code>	A <code>System.Int32</code> that specifies a character position in <code>s</code> .

Return Value

true if the character at position `index` in `s` is a member of the following category in `System.Globalization.UnicodeCategory`:
`System.Globalization.UnicodeCategory.Control`; otherwise, false.

Exceptions

Exception	Condition
<code>System.ArgumentNullException</code>	<code>s</code> is a null reference.
<code>System.ArgumentOutOfRangeException</code>	The value of <code>index</code> is less than zero, or greater than or equal to the length of <code>s</code> .

Char.IsControl(System.Char) Method

```
[ILAsm]  
.method public hidebysig static bool IsControl(valuetype System.Char c)  
  
[C#]  
public static bool IsControl(char c)
```

Summary

Determines whether the specified Unicode character is a control character.

Parameters

Parameter	Description
<i>c</i>	A Unicode character.

Return Value

true if *c* is a member of the following category in `System.Globalization.UnicodeCategory`: `System.Globalization.UnicodeCategory.Control`; otherwise, false.

Char.IsDigit(System.String, System.Int32) Method

```
[ILAsm]  
.method public hidebysig static bool IsDigit(string s, int32 index)  
  
[C#]  
public static bool IsDigit(string s, int index)
```

Summary

Determines whether the character at the specified position in the specified `System.String` is a decimal digit.

Parameters

Parameter	Description
<code>s</code>	A <code>System.String</code> .
<code>index</code>	A <code>System.Int32</code> that specifies a character position in <code>s</code> .

Return Value

true if the character at position `index` in `s` is a member of the following category in `System.Globalization.UnicodeCategory`:
`System.Globalization.UnicodeCategory.DecimalDigitNumber`; otherwise, false.

Description

[*Note:* `System.Char.IsDigit` determines if a `System.Char` is a radix-10 digit. This contrasts with `System.Char.IsNumber`, which determines if a `System.Char` is of any numeric Unicode category.]

Exceptions

Exception	Condition
-----------	-----------

System.ArgumentNullException	s is a null reference.
System.ArgumentOutOfRangeException	The value of <i>index</i> is less than zero, or greater than or equal to the length of s.

1
2
3

Char.IsDigit(System.Char) Method

```
[ILAsm]  
.method public hidebysig static bool IsDigit(valuetype System.Char c)  
  
[C#]  
public static bool IsDigit(char c)
```

Summary

Determines whether a Unicode character is a decimal digit.

Parameters

Parameter	Description
<i>c</i>	A Unicode character.

Return Value

true if *c* is a member of the following category in `System.Globalization.UnicodeCategory`:
`System.Globalization.UnicodeCategory.DecimalDigitNumber`; otherwise, false.

Description

[*Note:* `System.Char.IsDigit` determines if a `Char` is a radix-10 digit. This contrasts with `System.Char.IsNumber`, which determines if a `System.Char` is of any numeric Unicode category.]

Char.IsLetter(System.Char) Method

```
[ILAsm]  
.method public hidebysig static bool IsLetter(valuetype System.Char c)  
  
[C#]  
public static bool IsLetter(char c)
```

Summary

Determines whether the specified Unicode character is a letter.

Parameters

Parameter	Description
<i>c</i>	A Unicode character.

Return Value

true if *c* is a member of one of the following categories in `System.Globalization.UnicodeCategory`:
`System.Globalization.UnicodeCategory.UppercaseLetter`,
`System.Globalization.UnicodeCategory.LowercaseLetter`,
`System.Globalization.UnicodeCategory.TitlecaseLetter`,
`System.Globalization.UnicodeCategory.ModifierLetter`, or
`System.Globalization.UnicodeCategory.OtherLetter`; otherwise, false.

Char.IsLetter(System.String, System.Int32)

Method

```
[ILAsm]  
.method public hidebysig static bool IsLetter(string s, int32 index)  
  
[C#]  
public static bool IsLetter(string s, int index)
```

Summary

Determines whether the character at the specified position in the specified `System.String` is a letter.

Parameters

Parameter	Description
<code>s</code>	A <code>System.String</code> .
<code>index</code>	A <code>System.Int32</code> that specifies a character position in <code>s</code> .

Return Value

true if the character at position `index` in `s` is a member of one of the following categories in `System.Globalization.UnicodeCategory`:
`System.Globalization.UnicodeCategory.UppercaseLetter`,
`System.Globalization.UnicodeCategory.LowercaseLetter`,
`System.Globalization.UnicodeCategory.TitlecaseLetter`,
`System.Globalization.UnicodeCategory.ModifierLetter`, or
`System.Globalization.UnicodeCategory.OtherLetter`; otherwise, false.

Exceptions

Exception	Condition
System.ArgumentNullException	<code>s</code> is a null reference.
System.ArgumentOutOfRangeException	The value of <code>index</code> is less than zero, or greater

	than or equal to the length of s .
--	--------------------------------------

1

2

3

Char.IsLetterOrDigit(System.Char) Method

```
[ILAsm]  
.method public hidebysig static bool IsLetterOrDigit(valuetype System.Char  
c)  
  
[C#]  
public static bool IsLetterOrDigit(char c)
```

Summary

Determines whether the specified Unicode character is either a letter or a decimal digit.

Parameters

Parameter	Description
<i>c</i>	A Unicode character.

Return Value

true if *c* is a member of one of the following categories in `System.Globalization.UnicodeCategory`:
`System.Globalization.UnicodeCategory.UppercaseLetter`,
`System.Globalization.UnicodeCategory.LowercaseLetter`,
`System.Globalization.UnicodeCategory.TitlecaseLetter`,
`System.Globalization.UnicodeCategory.ModifierLetter`,
`System.Globalization.UnicodeCategory.OtherLetter`, or
`System.Globalization.UnicodeCategory.DecimalDigitNumber`; otherwise, false.

Char.IsLetterOrDigit(System.String, System.Int32) Method

```
[ILAsm]  
.method public hidebysig static bool IsLetterOrDigit(string s, int32  
index)
```

```
[C#]  
public static bool IsLetterOrDigit(string s, int index)
```

Summary

Determines whether the character at the specified position in the specified System.String is either a letter or a decimal digit.

Parameters

Parameter	Description
<i>s</i>	A System.String.
<i>index</i>	A System.Int32 that specifies a character position in <i>s</i> .

Return Value

true if the character at position *index* in *s* is a member of one of the following categories in System.Globalization.UnicodeCategory: System.Globalization.UnicodeCategory.UppercaseLetter, System.Globalization.UnicodeCategory.LowercaseLetter, System.Globalization.UnicodeCategory.TitlecaseLetter, System.Globalization.UnicodeCategory.ModifierLetter, System.Globalization.UnicodeCategory.OtherLetter, or System.Globalization.UnicodeCategory.DecimalDigitNumber; otherwise, false.

Exceptions

Exception	Condition
-----------	-----------

System.ArgumentNullException	s is a null reference.
System.ArgumentOutOfRangeException	The value of <i>index</i> is less than zero, or greater than or equal to the length of s.

1
2
3

Char.IsLower(System.Char) Method

```
[ILAsm]  
.method public hidebysig static bool IsLower(valuetype System.Char c)  
  
[C#]  
public static bool IsLower(char c)
```

Summary

Determines whether the specified Unicode character is a lowercase letter.

Parameters

Parameter	Description
<i>c</i>	A Unicode character.

Return Value

true if *c* is a member of the following category in `System.Globalization.UnicodeCategory`: `System.Globalization.UnicodeCategory.LowercaseLetter`; otherwise, false.

Char.IsLower(System.String, System.Int32) Method

```
[ILAsm]  
.method public hidebysig static bool IsLower(string s, int32 index)  
  
[C#]  
public static bool IsLower(string s, int index)
```

Summary

Determines whether the character at the specified position in the specified `System.String` is a lowercase letter.

Parameters

Parameter	Description
<code>s</code>	A <code>System.String</code> .
<code>index</code>	A <code>System.Int32</code> that specifies a character position in <code>s</code> .

Return Value

true if the character at position `index` in `s` is a member of the following category in `System.Globalization.UnicodeCategory`: `System.Globalization.UnicodeCategory.LowercaseLetter`; otherwise, false.

Exceptions

Exception	Condition
<code>System.ArgumentNullException</code>	<code>s</code> is a null reference.
<code>System.ArgumentOutOfRangeException</code>	The value of <code>index</code> is less than zero, or greater than or equal to the length of <code>s</code> .

Char.IsNumber(System.Char) Method

```
[ILAsm]  
.method public hidebysig static bool IsNumber(valuetype System.Char c)  
  
[C#]  
public static bool IsNumber(char c)
```

Summary

Determines whether the specified Unicode character is a number.

Parameters

Parameter	Description
<i>c</i>	A Unicode character.

Return Value

true if *c* is a member of one of the following categories in `System.Globalization.UnicodeCategory`:
`System.Globalization.UnicodeCategory.DecimalDigitNumber`,
`System.Globalization.UnicodeCategory.LetterNumber`, or
`System.Globalization.UnicodeCategory.OtherNumber`; otherwise, false.

Description

[*Note:* `System.Char.IsNumber` determines if a `System.Char` is of any numeric Unicode category. This contrasts with `System.Char.IsDigit`, which determines if a `System.Char` is a radix-10 digit.]

Char.IsNumber(System.String, System.Int32) Method

```
[ILAsm]  
.method public hidebysig static bool IsNumber(string s, int32 index)  
  
[C#]  
public static bool IsNumber(string s, int index)
```

Summary

Determines whether the character at the specified position in the specified `System.String` is a number.

Parameters

Parameter	Description
<code>s</code>	A <code>System.String</code> .
<code>index</code>	A <code>System.Int32</code> that specifies a character position in <code>s</code> .

Return Value

true if the character at position `index` in `s` is a member of one of the following categories in `System.Globalization.UnicodeCategory`:
`System.Globalization.UnicodeCategory.DecimalDigitNumber`,
`System.Globalization.UnicodeCategory.LetterNumber`, or
`System.Globalization.UnicodeCategory.OtherNumber`; otherwise, false.

Description

[*Note:* `System.Char.IsNumber` determines if a `System.Char` is of any numeric Unicode category. This contrasts with `System.Char.IsDigit`, which determines if a `System.Char` is a radix-10 digit.]

Exceptions

Exception	Condition
System.ArgumentNullException	s is a null reference.
System.ArgumentOutOfRangeException	The value of <i>index</i> is less than zero, or greater than or equal to the length of s.

1
2
3

Char.IsPunctuation(System.Char) Method

```
[ILAsm]  
.method public hidebysig static bool IsPunctuation(valuetype System.Char  
c)  
  
[C#]  
public static bool IsPunctuation(char c)
```

Summary

Determines whether the specified Unicode character is a punctuation mark.

Parameters

Parameter	Description
<i>c</i>	A Unicode character.

Return Value

true if *c* is a member of one of the following categories in `System.Globalization.UnicodeCategory`:
`System.Globalization.UnicodeCategory.ConnectorPunctuation`,
`System.Globalization.UnicodeCategory.DashPunctuation`,
`System.Globalization.UnicodeCategory.OpenPunctuation`,
`System.Globalization.UnicodeCategory.ClosePunctuation`,
`System.Globalization.UnicodeCategory.InitialQuotePunctuation`,
`System.Globalization.UnicodeCategory.FinalQuotePunctuation`, or
`System.Globalization.UnicodeCategory.OtherPunctuation`; otherwise, false.

Char.IsPunctuation(System.String, System.Int32) Method

```
[ILAsm]  
.method public hidebysig static bool IsPunctuation(string s, int32 index)  
  
[C#]  
public static bool IsPunctuation(string s, int index)
```

Summary

Determines whether the character at the specified position in the specified `System.String` is a punctuation mark.

Parameters

Parameter	Description
<code>s</code>	A <code>System.String</code> .
<code>index</code>	A <code>System.Int32</code> that specifies a character position in <code>s</code> .

Return Value

true if the character at position `index` in `s` is a member of one of the following categories in `System.Globalization.UnicodeCategory`:
`System.Globalization.UnicodeCategory.ConnectorPunctuation`,
`System.Globalization.UnicodeCategory.DashPunctuation`,
`System.Globalization.UnicodeCategory.OpenPunctuation`,
`System.Globalization.UnicodeCategory.ClosePunctuation`,
`System.Globalization.UnicodeCategory.InitialQuotePunctuation`,
`System.Globalization.UnicodeCategory.FinalQuotePunctuation`, or
`System.Globalization.UnicodeCategory.OtherPunctuation`; otherwise, false.

Exceptions

Exception	Condition
<code>System.ArgumentNullException</code>	<code>s</code> is a null reference.

System.ArgumentOutOfRangeException

The value of *index* is less than zero, or greater than or equal to the length of *s*.

1
2
3

Char.IsSeparator(System.String, System.Int32) Method

```
[ILAsm]
.method public hidebysig static bool IsSeparator(string s, int32 index)

[C#]
public static bool IsSeparator(string s, int index)
```

Summary

Determines whether the character at the specified position in the specified `System.String` is a separator character.

Parameters

Parameter	Description
<code>s</code>	A <code>System.String</code> .
<code>index</code>	A <code>System.Int32</code> that specifies a character position in <code>s</code> .

Return Value

true if the character at position `index` in `s` is a member of one of the following categories in `System.Globalization.UnicodeCategory`:
`System.Globalization.UnicodeCategory.SpaceSeparator`,
`System.Globalization.UnicodeCategory.LineSeparator`, or
`System.Globalization.UnicodeCategory.ParagraphSeparator`; otherwise, false.

Exceptions

Exception	Condition
System.ArgumentNullException	<code>s</code> is a null reference.
System.ArgumentOutOfRangeException	The value of <code>index</code> is less than zero, or greater than or equal to the length of <code>s</code> .

- 1
- 2
- 3

Char.IsSeparator(System.Char) Method

```
[ILAsm]  
.method public hidebysig static bool IsSeparator(valuetype System.Char c)  
  
[C#]  
public static bool IsSeparator(char c)
```

Summary

Determines whether the specified Unicode character is a separator character.

Parameters

Parameter	Description
<i>c</i>	A Unicode character.

Return Value

true if *c* is a member of one of the following categories in `System.Globalization.UnicodeCategory`:
`System.Globalization.UnicodeCategory.SpaceSeparator`,
`System.Globalization.UnicodeCategory.LineSeparator`, or
`System.Globalization.UnicodeCategory.ParagraphSeparator`; otherwise, false.

Char.IsSurrogate(System.String, System.Int32) Method

```
[ILAsm]  
.method public hidebysig static bool IsSurrogate(string s, int32 index)  
  
[C#]  
public static bool IsSurrogate(string s, int index)
```

Summary

Determines whether the character at the specified position in the specified `System.String` is a surrogate character.

Parameters

Parameter	Description
<code>s</code>	A <code>System.String</code> .
<code>index</code>	A <code>System.Int32</code> that specifies a character position in <code>s</code> .

Return Value

true if the character at position `index` in `s` is a member of the following category in `System.Globalization.UnicodeCategory`:
`System.Globalization.UnicodeCategory.Surrogate`; otherwise, false.

Exceptions

Exception	Condition
<code>System.ArgumentNullException</code>	<code>s</code> is a null reference.
<code>System.ArgumentOutOfRangeException</code>	The value of <code>index</code> is less than zero, or greater than or equal to the length of <code>s</code> .

Char.IsSurrogate(System.Char) Method

```
[ILAsm]
.method public hidebysig static bool IsSurrogate(valuetype System.Char c)

[C#]
public static bool IsSurrogate(char c)
```

Summary

Determines whether the specified Unicode character is a surrogate character.

Parameters

Parameter	Description
<i>c</i>	A Unicode character.

Return Value

true if *c* is a member of the following category in `System.Globalization.UnicodeCategory`: `System.Globalization.UnicodeCategory.Surrogate`; otherwise, false.

Char.IsSymbol(System.Char) Method

```
[ILAsm]  
.method public hidebysig static bool IsSymbol(valuetype System.Char c)  
  
[C#]  
public static bool IsSymbol(char c)
```

Summary

Determines whether the specified Unicode character is a symbol character.

Parameters

Parameter	Description
<i>c</i>	A Unicode character.

Return Value

true if *c* is a member of one of the following categories in `System.Globalization.UnicodeCategory`:
`System.Globalization.UnicodeCategory.MathSymbol`,
`System.Globalization.UnicodeCategory.CurrencySymbol`,
`System.Globalization.UnicodeCategory.ModifierSymbol`, or
`System.Globalization.UnicodeCategory.OtherSymbol`; otherwise, false.

Char.IsSymbol(System.String, System.Int32)

Method

```
[ILAsm]  
.method public hidebysig static bool IsSymbol(string s, int32 index)  
  
[C#]  
public static bool IsSymbol(string s, int index)
```

Summary

Determines whether the character at the specified position in the specified `System.String` is a symbol character.

Parameters

Parameter	Description
<code>s</code>	A <code>System.String</code> .
<code>index</code>	A <code>System.Int32</code> that specifies a character position in <code>s</code> .

Return Value

true if the character at position `index` in `s` is a member of one of the following categories in `System.Globalization.UnicodeCategory`:
`System.Globalization.UnicodeCategory.MathSymbol`,
`System.Globalization.UnicodeCategory.CurrencySymbol`,
`System.Globalization.UnicodeCategory.ModifierSymbol`, or
`System.Globalization.UnicodeCategory.OtherSymbol`; otherwise, false.

Exceptions

Exception	Condition
<code>System.ArgumentNullException</code>	<code>s</code> is a null reference.
<code>System.ArgumentOutOfRangeException</code>	The value of <code>index</code> is less than zero, or greater than or equal to the length of <code>s</code> .

- 1
- 2
- 3

Char.IsUpper(System.String, System.Int32)

Method

```
[ILAsm]  
.method public hidebysig static bool IsUpper(string s, int32 index)  
  
[C#]  
public static bool IsUpper(string s, int index)
```

Summary

Determines whether the character at the specified position in the specified `System.String` is an uppercase letter.

Parameters

Parameter	Description
<code>s</code>	A <code>System.String</code> .
<code>index</code>	A <code>System.Int32</code> that specifies a character position in <code>s</code> .

Return Value

true if the character at position `index` in `s` is a member of the following category in `System.Globalization.UnicodeCategory`: `System.Globalization.UnicodeCategory.UppercaseLetter`; otherwise, false.

Exceptions

Exception	Condition
<code>System.ArgumentNullException</code>	<code>s</code> is a null reference.
<code>System.ArgumentOutOfRangeException</code>	The value of <code>index</code> is less than zero, or greater than or equal to the length of <code>s</code> .

Char.IsUpper(System.Char) Method

```
[ILAsm]  
.method public hidebysig static bool IsUpper(valuetype System.Char c)  
  
[C#]  
public static bool IsUpper(char c)
```

Summary

Determines whether the specified Unicode character is an uppercase letter.

Parameters

Parameter	Description
<i>c</i>	A Unicode character.

Return Value

true if *c* is a member of the following category in `System.Globalization.UnicodeCategory`: `System.Globalization.UnicodeCategory.UppercaseLetter`; otherwise, false.

Char.IsWhiteSpace(System.String, System.Int32) Method

```
[ILAsm]  
.method public hidebysig static bool IsWhiteSpace(string s, int32 index)  
  
[C#]  
public static bool IsWhiteSpace(string s, int index)
```

Summary

Determines whether the character at the specified position in the specified `System.String` is a whitespace character.

Parameters

Parameter	Description
<code>s</code>	A <code>System.String</code> .
<code>index</code>	A <code>System.Int32</code> that specifies a character position in <code>s</code> .

Return Value

true if the character at position `index` in `s` either has a code point of 0x0009, 0x000a, 0x000b, 0x000c, 0x000d, 0x0085, 0x2028, or 0x2029; or is a member of the following category in `System.Globalization.UnicodeCategory`: `System.Globalization.UnicodeCategory.SpaceSeparator`; otherwise, false.

Exceptions

Exception	Condition
<code>System.ArgumentNullException</code>	<code>s</code> is a null reference.
<code>System.ArgumentOutOfRangeException</code>	The value of <code>index</code> is less than zero, or greater than or equal to the length of <code>s</code> .

- 1
- 2
- 3

Char.IsWhiteSpace(System.Char) Method

```
[ILAsm]  
.method public hidebysig static bool IsWhiteSpace(valuetype System.Char c)  
  
[C#]  
public static bool IsWhiteSpace(char c)
```

Summary

Determines whether the specified Unicode character is a whitespace character.

Parameters

Parameter	Description
<i>c</i>	A Unicode character.

Return Value

true if *c* either has a code point of 0x0009, 0x000a, 0x000b, 0x000c, 0x000d, 0x0085, 0x2028, or 0x2029; or is a member of the following category in `System.Globalization.UnicodeCategory`:
`System.Globalization.UnicodeCategory.SpaceSeparator`; otherwise, false.

Char.Parse(System.String) Method

```
[ILAsm]  
.method public hidebysig static valuetype System.Char Parse(string s)  
  
[C#]  
public static char Parse(string s)
```

Summary

Returns the specified `System.String` converted to a `System.Char` value.

Parameters

Parameter	Description
s	A <code>System.String</code> containing a single Unicode character.

Return Value

The `System.Char` value obtained from s.

Exceptions

Exception	Condition
<code>System.ArgumentNullException</code>	s is a null reference.
<code>System.FormatException</code>	s does not contain exactly one character.

Char.ToLower(System.Char) Method

```
[ILAsm]
.method public hidebysig static valuetype System.Char ToLower(valuetype
System.Char c)

[C#]
public static char ToLower(char c)
```

Summary

Converts a System.Char to its lowercase equivalent.

Parameters

Parameter	Description
<i>c</i>	A Unicode character.

Return Value

The lowercase equivalent of *c*, or the value of *c* if and only if *c* is already lowercase or does not have a lowercase equivalent.

Example

The following example demonstrates the System.Char.ToLower method.

```
[C#]

using System;
public class CharToLower {
    public static void Main() {
        Char[] cAry = {'A', 'c', '*'};
        foreach (Char c in cAry) {
            Console.WriteLine("Char '{0}' ToLower is ", c);
            Console.WriteLine("{0}", Char.ToLower(c));
        }
    }
}
```

The output is

Char 'A' ToLower is a

```
1
2 Char 'c' ToLower is c
3
4
5 Char '*' ToLower is *
6
7
```

Char.ToString() Method

```
[ILAsm]  
.method public hidebysig virtual string ToString()  
  
[C#]  
public override string ToString()
```

Summary

Returns a `System.String` representation of the value of the current instance.

Return Value

A `System.String` representation of the current instance.

Description

[*Note:* This method overrides `System.Object.ToString.`]

Char.ToString(System.IFormatProvider)

Method

```
[ILAsm]  
.method public final hidebysig virtual string ToString(class  
System.IFormatProvider provider)  
  
[C#]  
public string ToString(IFormatProvider provider)
```

Summary

Converts the value of this instance to its equivalent `String` representation using the specified culture-specific format information.

Parameters

Parameter	Description
<i>provider</i>	(Reserved) An <code>System.IFormatProvider</code> interface implementation that supplies culture-specific formatting information.

Return Value

The `System.String` representation of the value of this instance as specified by *provider*.

Description

provider is ignored; it does not participate in this operation.

Char.ToUpper(System.Char) Method

```
[ILAsm]  
.method public hidebysig static valuetype System.Char ToUpper(valuetype  
System.Char c)  
  
[C#]  
public static char ToUpper(char c)
```

Summary

Converts a System.Char to its uppercase equivalent.

Parameters

Parameter	Description
<i>c</i>	A Unicode character.

Return Value

The uppercase equivalent of *c*, or the value of *c* if and only if *c* is already uppercase or does not have an uppercase equivalent.

Example

The following example demonstrates the System.Char.ToUpper method.

```
[C#]  
  
using System;  
public class CharToUpper {  
    public static void Main() {  
        Char[] cAry = {'A', 'c', '*'};  
        foreach (Char c in cAry) {  
            Console.Write("Char '{0}' ToUpper is {1}",  
                c, Char.ToUpper(c));  
            Console.WriteLine();  
        }  
    }  
}
```

The output is

Char 'A' ToUpper is A

```
1
2
3 Char 'c' ToUpper is C
4
5
6 Char '*' ToUpper is *
7
8
```